






















SEMNALIZARE

Console acustice si luminoase

Tip	Nivel de zgomot	Dimensiuni (HxLxA) mm	Distanța maximă de recepție a semnalului conform EN54-23 în metri (m)					Putere	Grad de protecție	Produs
			2	46	90	134	178			
DSF 5	105 dB (A)	263,5 x 133,5 x 143						13 Joules	IP 66 IP 67	
DSF 10	110 dB (A)							13 Joules		
P 22 DBF	80 dB (A)	Ø 29 x 52							IP 40	
SON 4	100 dB (A)	86 x 86 x AC: 120 / DC: 102						0,25 Joules	IP 56	
SON 4L										
PA X 1-05	100 dB (A)	172,4 x 109,5 x 80,6						5 Joules	IP 66	
PA X 5-05	105 dB (A)	215 x 163,4 x 132						5 Joules		
PA X 5-10								10 Joules		
PA X 10-10	110 dB (A)	270 x 214 x 156						10 Joules	IP 66	
PA X 10-15								15 Joules		
PA X 20-10	120 dB (A)	270 x 214 x 181						10 Joules	IP 66	
PA X 20-15								15 Joules		
PA X MA-05	100 dB (A)	134,2 x 166 x 114						5 Joules	IP 66 IK 08	
PA X MA-10								10 Joules		

Dispozitive acustice tip coloana

Tip	Nivel de zgomot	Dimensiuni (HxLxA) mm	Culori leduri	Grad de protecție	Produs
BR35	75 dB (A)	Ø 35	transparent, galben, chihlimbar, rosu, verde, albastru	IP54	
BR50	85 dB (A)	Ø 54	transparent, galben, chihlimbar, rosu, verde, albastru	IP54 (IP65)	