

## CS 028 / CSL 028

### Caracteristici Tehnice

- temperatura suprafetei: 150W/250W: max.+50°C, 400W: max.+65°C
- ventilator axial: CS 028: 13.8m<sup>3</sup>/h  
CSL 028: 45m<sup>3</sup>/h (230V AC); 54m<sup>3</sup>/h (120V AC)
- montaj pe sina DIN, sau cu surub Ø 5.3mm
- temperatura de functionare: -45~ +70° C
- grad de protectie: IP20



Model	Fixare sina DIN	Fixare cu Surub	Capacitate de incalzire	Curent	Tensiune	Dimensiuni
CS 028	02800.0-00	02800.0-01	150W	12A	230VAC	75 x 65 x 90 mm
CSL 028	02811.0-00	02811.0-01	250W	9A	230VAC	90 x 85 x 111 mm
CSL 028	02810.0-00	02810.0-01	400W	15A	230VAC	90 x 85 x 111 mm
CS 028	02800.9-00	02800.9-01	150W	6A	120VAC	75 x 65 x 90 mm
CSL 028	02811.9-00	02811.9-01	250W	6A	120VAC	90 x 85 x 111 mm
CSL 028	02810.9-00	02810.9-01	400W	9A	120VAC	90 x 85 x 111 mm

