


PF 42.500 EMC

Caracteristici	IP 54	IP 55	Produs
Cod	11842101055	11842103055	
Cod (piese de schimb) filtru mat (1 set = 5 buc)	18611600032	18611600036	
Cod (piese de schimb) ventilator 230V AC		18611000033	
Tensiune nominala ±10%	230 V 50 / 60 Hz		
Design (carcasa protejata atingerii accidentale ale ventilatorului)	realizat din material termoplastic turnat prin injectie, cu proprietati de auto-stingere, UL 94 VO		
Material folosit - EMC	inox		
Durata de viata L ₅₀ (+ 40 °C)	40,000 h		
Greutate / Culoare	1.18 kg / RAL 7035		
Nivel zgomot (EN ISO 3741)	40 / 43 dB (A)		
Mod de conectare	conector cu arc		
Tipul rulmentului	rulment cu bile		
Aprobari	UL, cUL, CE, (la cerere: GOST)		
Putere consumata	18 / 17 W		
Latime x lungime x adancime	252 x 252 x 103 mm		
Dimensiuni decupare	224 x 224 mm		
Grad de protectie (EN 60529 / UL 50)	tip NEMA 12 filtru standard	tip NEMA 12 filtru pliat	
Filtru mat,clasa filtrare	G 3	G 4	
Volum de aer pana la	171 m ³ /h		
Volum de aer nefiltrat	156 / 171 m ³ /h	145 / 160 m ³ /h	
Volum de aer filtrat (PF + PFA 40.000)	116 / 127 m ³ /h	109 / 113 m ³ /h	
Eficienta de filtrare	88%	91%	