


**PF 65.000 EMC**

Caracteristici	IP 54	IP 55	Produs
Cod	11865102055	11865103055	
Cod (piese de schimb) filtru mat (1 set = 5 buc)	18611600033	18611600037	
Cod (piese de schimb) ventilator 230V AC		18611000044	
Tensiune nominala ±10%	230 V 50 / 60 Hz		
Design (carcasa protejata atingerii accidentale ale ventilatorului)	realizat din material termoplastic turnat prin injectie, cu proprietati de auto-stingere, UL 94 VO		
Material folosit - EMC	inox		
Durata de viata L <sub>50</sub> (+ 40 °C)	40,000 h		
Greutate / Culoare	3,43 kg / RAL 7035		
Nivel zgomot (EN ISO 3741)	54 / 52 dB (A)		
Mod de conectare	conector cu arc		
Tipul rulmentului	rulment cu bile		
Aprobari	UL, cUL, CE, (la cerere: GOST)		
Putere consumata	65 / 80 W		
Latime x lungime x adancime	320 x 320 x 157 mm		
Dimensiuni decupare	292 x 292 mm		
Grad de protectie (EN 60529 / UL 50)	tip NEMA 12 filtru standard	tip NEMA 12 filtru pliat	
Filtru mat,clasa filtrare	G 3	G 4	
Volum de aer pana la	505 m <sup>3</sup> /h		
Volum de aer nefiltrat	480 m <sup>3</sup> /h	505 m <sup>3</sup> /h	
Volum de aer filtrat (PF + PFA 60.000)	370 m <sup>3</sup> /h	380 m <sup>3</sup> /h	
Eficienta de filtrare	91%	91%	