


PF 66.000

| Caracteristici | IP 54 | IP 55 | Produs |
|---|--|-----------------------------|---|
| Cod | 11666102055 | 11666103055 |  |
| Cod (piese de schimb) filtru mat (1 set = 5 buc) | 18611600033 | 18611600037 | |
| Cod (piese de schimb) ventilator 230V AC | | 18611000045 | |
| Tensiune nominala ± 10% | 230 V 50 / 60 Hz | | |
| Design (carcasa protejata atingerii accidentale ale ventilatorului) | realizat din material termoplastic turnat prin injectie, cu proprietati de auto-stingere, UL 94 VO | | |
| Durata de viata L ₅₀ (+ 40 °C) | 40,000 h | | |
| Greutate | 3.2 kg | | |
| Culoare | RAL 7035 | | |
| Nivel zgomot (EN ISO 3741) | 63 / 64 dB (A) | | |
| Mod de conectare | conector cu arc | | |
| Tipul rulmentului | rulment cu bile | | |
| Aprobari | UL, cUL, CE, (la cerere: GOST) | | |
| Putere consumata | 115 / 150 W | | |
| Latime x lungime x adancime | 320 x 320 x 157 mm | | |
| Dimensiuni decupare | 291 x 291 mm | | |
| Grad de protectie (EN 60529 / UL 50) | tip NEMA 12 filtru standard | tip NEMA 12 filtru pliat | |
| Filtru mat,clasa filtrare | G 3 | G 4 | |
| Volum de aer pana la | 785 m ³ /h | | |
| Volum de aer nefiltrat | 640 / 653 m ³ /h | 770 / 785 m ³ /h | |
| Volum de aer filtrat (PF + PFA 60.000) | 445 / 445 m ³ /h | 490 / 501 m ³ /h | |
| Eficienta de filtrare | 91% | 91% | |